


---

 TECHNICAL DATA SHEET

# ABB cable glands – STX Star Teck® series

## Hazardous locations



STX is the original STAR TECK® Explosion Proof fitting for Teck, MC and ACWU - its innovative design provides quality engineering, easier installation and helps achieve safer, more reliable terminations in challenging industrial environments.

**Certifications / Standards:**



---

**IMPORTANT:**

Must be installed with the SC4-KIT-1 sealing compound or the SC65 putty sealing compound. Sold separately. See sealing compounds information.

---

**Features & Benefits:**

- Excellent solution for hazardous location
- Excellent pullout strength
- Robust metallic construction
- Quick and easy installation without disassembly
- Provides grounding continuity of cable armor
- Splined gland and gripping features for ease of installation

---

**Applications:**

- Provides means for passing jacketed metal clad cables through a bulkhead or enclosure in industrial and hazardous areas
- Oil and gas Industry, chemical and industrial markets
- Construction and installation zones where metal clad cables are specified
- Suitable for cable types:
  - Jacketed Teck and ACWU
  - Armored control and instrument (ACIC Div2 locations)
  - Type MC: Jacketed corrugated metal clad (aluminum and steel)

---

**Material:**

- Copper free aluminum
- Zinc plated steel option
- PVC coating available for both materials option

---

**Sealing compounds information:**

- Use SC4-KIT-1 liquid compound for shielded cables and cables with 5 conductors or more (including ground).
- The SC65 is not recommended for use with shielded cables. Suitable for use on cables with a maximum of 4 conductors (including ground).
- Approximate Sealing Compound Volumes:
  - SC4-KIT-1 = 50cc / SC65 = 34cc

---

**Environmental ratings:**
**Working Temperature:**

- Normal use -40 to +90°C (-40 to +194°F)

**Ingress protection:**

- Type 4 / 4X

---

**Conforms to:**

- CSA 22.2-25/ -30/ -174/ -94
  - Class I Div1 ABCD Class II Div1 EFG Class III Div1
- UL2225
  - Class I Div1 ABCD Class II Div1 EFG Class III Div1
- UL514B and CSA C22.2-18.3
  - Wet and Dry Locations
- RoHS (Restriction of Hazardous Substances Directive) 2011/65/EU Incorporating 2015/863 amendment to Annex II

Product selection										
Part no:	Thread (NPT)	Max. Vol. of sealing compound	Range over jacket		Range over armour		Nominal dimensions			
			Min	Max	Min	Max	A	B	C	D
STX050-462	1/2	5	13.34	16.51	10.54	14.48	20.07	63.50	41.40	10.03
			(0.525)	(0.650)	(0.415)	(0.570)	(0.790)	(2.500)	(1.630)	(0.395)
STX050-464	1/2	5	15.24	19.30	12.45	17.27	20.07	63.50	41.40	12.32
			(0.600)	(0.760)	(0.490)	(0.680)	(0.790)	(2.500)	(1.630)	(0.485)
STX075-465	3/4	8	18.42	22.48	15.62	20.45	20.07	66.55	46.23	15.42
			(0.725)	(0.885)	(0.615)	(0.805)	(0.790)	(2.620)	(1.820)	(0.607)
STX075-466	3/4	8	20.96	25.02	18.16	22.99	20.07	66.55	46.23	18.16
			(0.825)	(0.985)	(0.715)	(0.905)	(0.790)	(2.620)	(1.820)	(0.715)
STX100-467	1	16	22.35	27.05	19.56	25.02	25.02	71.88	61.98	19.05
			(0.880)	(1.065)	(0.770)	(0.985)	(0.985)	(2.830)	(2.440)	(0.750)
STX100-468	1	16	26.04	30.61	23.24	28.58	25.02	71.88	61.98	22.73
			(1.025)	(1.205)	(0.915)	(1.125)	(0.985)	(2.830)	(2.440)	(0.895)
STX125-469	1-1/4	23	30.15	34.93	27.36	32.89	25.65	77.47	64.01	26.85
			(1.187)	(1.375)	(1.077)	(1.295)	(1.010)	(3.050)	(2.520)	(1.057)
STX150-470	1-1/2	43	34.29	41.28	31.50	39.24	26.16	95.50	83.31	29.90
			(1.350)	(1.625)	(1.240)	(1.545)	(1.030)	(3.760)	(3.280)	(1.177)
STX150-550	1-1/2	43	38.10	41.28	35.31	39.24	26.16	95.50	83.31	34.67
			(1.500)	(1.625)	(1.390)	(1.545)	(1.030)	(3.760)	(3.280)	(1.365)
STX150-471	1-1/2	43	40.64	47.63	37.85	45.59	26.16	95.50	83.31	37.21
			(1.600)	(1.875)	(1.490)	(1.795)	(1.030)	(3.760)	(3.280)	(1.465)
STX200-472	2	72	43.18	49.91	40.39	47.88	26.92	102.87	92.46	39.42
			(1.700)	(1.965)	(1.590)	(1.885)	(1.060)	(4.050)	(3.640)	(1.552)
STX200-473	2	72	48.26	55.55	45.47	53.52	26.92	102.87	92.46	44.50
			(1.900)	(2.187)	(1.790)	(2.107)	(1.060)	(4.050)	(3.640)	(1.752)
STX200-474	2	72	53.34	60.33	50.55	57.91	26.92	105.41	102.87	50.55
			(2.100)	(2.375)	(1.990)	(2.280)	(1.060)	(4.150)	(4.050)	(1.990)
STX250-475	2-1/2	147	58.42	65.15	55.63	63.12	40.13	109.47	115.32	55.37
			(2.300)	(2.565)	(2.190)	(2.485)	(1.580)	(4.310)	(4.540)	(2.180)
STX250-476	2-1/2	147	63.50	69.85	60.71	67.46	40.13	109.47	115.32	59.94
			(2.500)	(2.750)	(2.390)	(2.656)	(1.580)	(4.310)	(4.540)	(2.360)
STX300-478	3	286	65.53	72.14	61.98	69.85	41.66	143.26	125.22	62.36
			(2.580)	(2.840)	(2.440)	(2.750)	(1.640)	(5.640)	(4.930)	(2.455)
STX300-479	3	286	70.87	77.72	67.06	75.44	41.66	147.32	133.35	67.44
			(2.790)	(3.060)	(2.640)	(2.970)	(1.640)	(5.800)	(5.250)	(2.655)
STX350-480	3-1/2	366	76.20	83.06	72.90	81.03	42.93	160.53	147.07	72.62
			(3.000)	(3.270)	(2.870)	(3.190)	(1.690)	(6.320)	(5.790)	(2.859)
STX350-481	3-1/2	366	81.53	88.39	77.27	86.11	42.93	160.53	147.07	77.65
			(3.210)	(3.480)	(3.042)	(3.390)	(1.690)	(6.320)	(5.790)	(3.057)
STX400-482	4	614	86.87	93.73	83.06	91.19	44.20	168.40	157.23	83.44
			(3.420)	(3.690)	(3.270)	(3.590)	(1.740)	(6.630)	(6.190)	(3.285)
STX400-483	4	614	91.69	98.30	87.38	95.76	44.20	168.40	157.23	87.76
			(3.610)	(3.870)	(3.440)	(3.770)	(1.740)	(6.630)	(6.190)	(3.455)
STX400-484	4	614	96.77	102.36	91.44	99.82	44.20	180.09	175.26	92.08
			(3.810)	(4.030)	(3.600)	(3.930)	(1.740)	(7.090)	(6.900)	(3.625)
STX400-485	4	614	100.71	106.30	95.38	103.25	44.20	180.09	175.26	95.76
			(3.965)	(4.185)	(3.755)	(4.065)	(1.740)	(7.090)	(6.900)	(3.770)

To order steel version, add suffix "S". Ex: STX050-464S.

To order with PVC coating, add suffix "PVC". Ex: STX050-464SPVC. Contact your representative for availability.

Dimensions may vary depending on material selection.

Note: Product must be installed in accordance with applicable national and local electrical codes.

